

CEA-2006-A SPECIFICATIONS

POWER RATING: 75 Watts per channel @ 4 Ohms < 1% THD+N
SN RATIO: >87 dBA (reference: 1 Watt into 4 Ohms)

GT Trading SPECIFICATIONS (Tcase = 25 °C / 4 Ohms stereo / 0.17V input level if not otherwise specified)

POWER RATINGS:
 75Watts per channel @ 4 Ohms < 0.3% THD+N
 105Watts per channel @ 2 Ohms < 0.3% THD+N
 210Watts BTL mode @ 4 Ohms < 0.3% THD+N

Power output @ 4 Ohm / 14V4 / 1KHz / STEREO / 0.3% THD: 75W x 4 – 35.5A – 69.2 % efficiency
Power output @ 2 Ohm / 14V4 / 1KHz / STEREO / 0.3% THD: 105 W x 4 – 57 A – 60.4 % efficiency
Power output @ 4 Ohm / 14V4 / 1KHz / BRIDGE / 0.3% THD: 210 W x 2 – 59 A – 60.4 % efficiency

THD @ 4 Ohm / 14V4 / STEREO: < 0.04 % (1KHz / Power rating ref)
THD @ 2 Ohm / 14V4 / STEREO: < 0.04 % (1KHz / Power rating ref)
THD @ 4 Ohm / 14V4 / BRIDGE: < 0.04 % (1KHz / Power rating ref)
DIM @ 4 Ohm / 14V4 / STEREO: < 0.01 % (Power rating ref)
DIM @ 2 Ohm / 14V4 / STEREO: < 0.02 % (Power rating ref)
DIM @ 4 Ohm / 14V4 / BRIDGE: < 0.02% (Power rating ref)

DC-DC converter typology: **Unregulated**
Conversion frequency: **40 KHz (± 6 %)**
Absolute maximum operation supply voltage range: **10 V ÷ 16 V**
Recommended operation supply voltage range: **11 V ÷ 14.4 V**
Undervoltage cutoff Threshold: **8.5 V**
Mute delay time: **3 secs.**
Secondary voltages (Amp. / Driver / Pre.) @ 14.4 Volt: **±39 V / ±7.5 V / ±14.8 V**
Max output offset voltage (each channel): **±20 mV**
Standby current @ 14.4 Volt: **< 2 mA**
Quiescent consumption @ 12.6 Volt / 14.4 Volt: **0.49 A / 0.54 A (no idle current regulation)**
Idle current regulation @ 14.4 Volt (4 Ohm STEREO - no signal): **0.1 A (each channel)**
Quiescent consumption @ 12.6 Volt / 14.4 Volt: **0.65 A / 0.74 A (with 0.2 A total idle current regulation)**
Thermal protection consumption @ 14.4 Volt: **0.67 A**
Battery ground vs secondary ground decoupling: **R.C.D. network (56R // 100n // double clamp diodes)**
Body ground vs battery ground decoupling: **R.C. network (100R // 100n)**
Bandwidth (-3dB ÷ 1 Watt) @ 14.4 Volt (4 Ohm STEREO): **5 Hz ÷ 150 KHz**
Input sensitivity @ 14.4 Volt (4 Ohm STEREO) – Power rating ref: **0.17 V ÷ 4.3 V**
Input impedance @ 1 KHz (STEREO input): **11 KOhm**
Input capacitance @ 1 KHz (STEREO input): **220 pF**
Input ground decoupling: **R.C. network (15R // 100n)**
S/N ratio (AP filter 10 Hz - 500 KHz) – Power rating ref: **91 dB**
S/N ratio (AP filter 10 Hz - 22 KHz) – Power rating ref: **107 dB (“A” weighted)**
Eq. Input noise (AP filter 10 Hz - 500 KHz): **4.8 uV**
Eq. Input noise (AP filter 10 Hz - 22 KHz): **0.76 uV (“A” weighted)**
Channel separation @ 100Hz / 1KHz / 10KHz – Power rating ref: **88 dB / 74 dB / 57 dB**
Xover functions: **HIGH Pass & LOW Pass (BAND Pass allowed)**
 (20 ÷ 150Hz) & (45 ÷ 300Hz)
12 dB/oct - 0.6 (Stereo & Mono)
88 °C (±5°C)
50 °C (±5°C)
391 / 299 (Right / Left)
458 / 335 (Right / Left)
290 / 219 (Right / Left)
8.7 mOhm / 11.9 mOhm (Right / Left)
2 Ohm / 4 Ohm (Stereo / Bridged)
2 x 30 A (Internal)

Filter slope - Filter "Q":
Thermal cutoff Threshold:
INTELLISPEED® start Threshold:
Damping factor @ 100 Hz (4 Ohm STEREO) - 10 Watt ref:
Damping factor @ 1 KHz (4 Ohm STEREO) - 10 Watt ref:
Damping factor @ 10 KHz (4 Ohm STEREO) - 10 Watt ref:
Output impedance @ 1 KHz (4 Ohm STEREO) - 10 Watt ref:
Overload cutoff @ 14.4 Volt:
Suggested fuse: